## CONCRETE PLACEMENT & FINISHING SYSTEMS

## REFLECTIFIER® CONCRETE PLACEMENT & FINISHING DENSIFIER

**ReflectiFIER**<sup>®</sup> is a non-film forming, fast-acting hydrophobic treatment applied on new concrete during the placement and finishing process. Single spray-on-leave-on application penetrates the slab up to ½" inch (13mm) in depth, cross-linking with ReflectiXTENDER<sup>®</sup> Concrete Placement & Finishing Aid resulting in an easily workable, densely consolidated, and highly refined concrete surfaces.

ReflectiFIER<sup>®</sup> also chemically reacts with the concrete matrix, creating new cementitious compounds and closing capillaries resulting in the slab being densified into a solid mass. Creates a sustainable, extremely abrasion resistant, dust proof surface profile that extends its service life and performance while also improving energy performance and insulation qualities for Green Initiatives.

Save time and money by completing the project ahead of schedule with Reflective Floor<sup>®</sup> Concrete Placement & Finishing Systems.

#### TECHNICAL INFORMATION

Appearance	Clear / White
рН	10.5 - 11.5
VOC Content	<50 g/L
Flash Point	Not Flammable
Freezing Point	32°F - 0°C
Shelf Life	18 Months, Unopened

#### APPLICATION RATES

#### 300 SF<sup>2</sup> / Gal. (7.36 m<sup>2</sup>/L)

Applications Required: 1

Coverage rates & drying times will vary due to the wide variety of differences in concrete's quality, porosity, temperature, and relative humidity.

#### PACKAGING

5 Gallon Pails // 18.9 L
55 Gallon Drums // 208 L
275 Gallon Totes // 1,040 L

#### STORAGE & HANDLING

Do not allow product to freeze. Store in a well ventilated, cool, dry location and maintain temperatures between  $40^{\circ}$  - $100^{\circ}$  F (4° - 38° C). Do not alter or mix with other chemicals. Maintain unused product in the original container. Any container that cannot be saved for recovery or recycling should be triple rinsed and disposed of in accordance with local, state, and federal regulations.

#### ADVANTAGES

- Penetrates to a depth of 1/2" inch (13 mm)
- Dust Proofs
- Excellent Water Repellent
- Harder, Denser Surface
- Increases Life Expectancy & Performance
- Protects & Enhances Stained, Integral Color & Dyed Decorative Surfaces
- Preserves the Natural Look of Concrete
- Blocks Efflorescence & Prevents ASR
- Resistant to Blushing & Does Not Yellow
- Will not Chip, Peel, Flake with Age or Exposure
- Contributes to Green Initiatives
- Cross-Links with ReflectiXTENDER<sup>®</sup> Concrete Placement & Finishing Aid

#### INDUSTRY SPECIFICATIONS & COMPLIANCE

- ASTM E 96-10
- ASTM C 944
- ASTM C 779
- ASTM C 1583
- USDA Compliant
- FDA Approved



# CONCRETE PLACEMENT & FINISHING AID

Reflective Floor® Concrete Placement & Finishing System is a methodical process requiring the use of three\* separate products and must be used in sequential order to attain maximum results.

#### APPLICATION DIRECTIONS

Apply a fine spray uniformly onto the surface using a High-Volume, Low-Pressure manual or commercial grade sprayer at a coverage rate of 300 SF<sup>2</sup>/gal. (7.36 m<sup>2</sup>/L) immediately after the completion of the power troweling process.

Work the product into the surface using a fox-tail broom. Keep surface wet with ReflectiFIER® Concrete Densifier for a minimum of 30 minutes. Spread any excess of product &/or apply additional product as needed to areas that become dry to maintain surface saturation.

Allow ReflectiFIER<sup>®</sup> to air dry completely.

ReflectiFIER<sup>®</sup> is part of Reflective Floor's Concrete Placement & Finishing System (CPF) and must be used only after ReflectiXTENDER<sup>®</sup> has been applied. Never use ReflectiFIER<sup>®</sup> as a stand-alone product.

\*Do NOT use any type of Guard/Sealer after ReflectiFIER® if the finished floor is specified for a grind and polish.

#### CLEAN UP // DISPOSAL

Use soap and water. Any product that cannot be saved or recycled should be triple rinsed and disposed of according to local, state, and federal regulations.

#### MAINTENANCE

Routine cleaning with ReflectiCLEAN<sup>®</sup> Concrete Cleaner is recommended using a micro-fiber mop or auto scrubber equipped with soft pads. Do NOT use string mops. DO NOT USE cleaners that have butyl compounds or citrus, these acidic cleaners will damage the floor.

#### SAFETY & FIRST AID

**WARNING:** Harmful if swallowed. Harmful in contact with skin. Causes serious eye irritation. Harmful if inhaled. Keep out of reach of children. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area.

**IF SWALLOWED:** Call a POISON CENTER or doctor or physician immediately. Rinse mouth. DO NOT INDUCE VOMITING. **SKIN:** Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. **EYES:** Flush with water immediately for 15 minutes. Remove contact lenses if present and easy to do, continue rinsing. **INHALED:** Move person to fresh air. If not breathing, give rescue breathing and contact medical attention/911. If breathing is difficult, give oxygen. If symptoms persist, consult medical advice.

Always read in full product SDS for additional precautionary instructions before use. Use appropriate Personal Protection Equipment (PPE) during application and handling.

24 Hour Emergency Telephone: INFOTRAC (800) 535-5053 (US & Canada) (352) 323-3500 (International)

#### WARRANTY

Reflective Floor<sup>®</sup> solely and expressly warrants that for 12 months from the date of purchase of Reflective Floor<sup>®</sup> products shall be free from defects in materials and workmanship, but only to the extent that the product is properly installed only by Reflective Floor<sup>®</sup> Certified Installers in accordance with its product literature and in strict compliance with the installation information and instructions in the product literature and label(s).

It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer does not have control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing the proven defective Reflective Floor<sup>®</sup> product. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

### C

CUSTOMER SERVICE: +1 856-REFLECT (733-5328)

FOR MORE INFORMATION AND PRODUCT SPECIFICATIONS: Visit us at www.ReflectiveFloor.com

Reflective Floor® and Reflecti® family of product logos and names are trademarks under license. All Rights Reserved. Patented, other patents pending.

